



**POWER-PACK® Standard Conveyors - built the way you want them...**

Field Info Required	Data	Field Info Required	Data
A. Conveyor Length O.A.		Total Load On Conveyor	
B. Belt Width		Belt Speed In Fpm	
C. Height T.O.B. ( Top of Belt )		Power: Volts, Phase, Hz	
B-B. Belt Opening		S. Conveyor Angle	
M. Top of Belt @ Bottom			
Product Being Carried:			
Adverse Condition If Any:			

**Power-Pack will size for application**

Dimensions	Belt Width +	Light	Medium	Heavy
D. Body Height		8.125"	10.125"	12.25"
E. Body Width O. A.	Belt +	4.25"	4.25"	5.25"
F. Tail End Width O. A.	Belt +	4.5"	6.25"	9.25"
G. Drive End Width O. A.	Belt +	13.5"	15.25"	18.25"
H. Belt Tension Take-Up Adjustment		2.5"	5"	11"
Q. Load Height	M. +	5"	5"	5"
Drive & Tail Pulley: <b>Crowned</b>		4.5"	6.625"	8.625"
V. Sidewall Height		2"	2"	3"

**Standard Features**

Body Construction : <b>Mild Steel</b>	Bed Type : <b>Slider</b>
Belt Type : <b>PVC</b>	Belt Lacers: <b>Clipper Lacer</b>
Motor-Reducer Style : <b>TEFC-Shaft Mounted</b>	Return Idlers: <b>Greased Packed Bearings</b>
Motor Location : <b>Left Side</b>	Leg Support: <b>Tri-Lock H style</b>
Bearings : <b>Greased Sealed, Self Aligning</b>	Cleats: <b>PVC 1-1/2" High on 12" Centers</b>

**See options section for additional features**

**Power-Pack® Conveyor Company**  
 38363 Airport Parkway • Willoughby, OH 44094  
 Phone: (440) 975-9955 • Fax: (440) 975-0505  
 Website: [www.power-packconveyor.com](http://www.power-packconveyor.com)  
 Email: [ppcc@power-packconveyor.com](mailto:ppcc@power-packconveyor.com)



**Safety Features:** Patented Concealed Bearings,  
 Patented Concealed Drive & Tail Rolls,  
 Patented Boltless, Bearing Slide Mounts