



**POWER-PACK® Standard Conveyors - built the way you want them...**

Field Info Required	Data	Field Info Required	Data
A. Conveyor Length O.A.		Total Load On Conveyor	
B. Belt Width		Belt Speed In Fpm	
C. Height T.O.B. ( Top of Belt )		Power: Volts, Phase, Hz	
M. Top of Belt @ Bottom		S. Conveyor Angle	
Product Being Carried:			
Adverse Condition If Any:			
<b>Power-Pack will size for application</b>			

Dimensions	Belt Width +	Light	Medium	Heavy
D. Body Height		8.125"	10.125"	12.25"
E. Body Width O. A.	Belt +	4.25"	4.25"	5.25"
F. Tail End Width O. A.	Belt +	4.5"	6.25"	9.25"
G. Drive End Width O. A.	Belt +	13.5"	15.25"	18.25"
Q. Load Height ( Top of Flapper )	M. +	5"	5"	5"
H. Belt Tension Take-Up Adjustment		2.5"	5"	11"
Drive & Tail Sprocket Diam.		4"	6"	8"

Standard Features			
Body Construction : <b>Mild Steel</b>		Bed Type : <b>Slider with Plastic wear strips</b>	
Belt Type : <b>1" x 1", Galvanized Flat Mesh</b>		Belt Lacers : <b>Pin</b>	
Motor-Reducer Style : <b>TEFC-Shaft Mounted</b>		Return Idlers : <b>Greased Packed Bearings</b>	
Motor Location : <b>Left Side</b>		Leg Support : <b>Tri-Lock H style</b>	
Bearings : <b>Greased Sealed, Self Aligning</b>		Cleats : <b>Steel Angle x 1-1/2" @ 12" Centers</b>	
K. Sides : <b>4" Formed Channel</b>			
<b>See options section for additional features</b>			

**Power-Pack® Conveyor Company**  
 38363 Airport Parkway • Willoughby, OH 44094  
 Phone: (440) 975-9955 • Fax: (440) 975-0505  
 Website: [www.power-packconveyor.com](http://www.power-packconveyor.com)  
 Email: [ppcc@power-packconveyor.com](mailto:ppcc@power-packconveyor.com)



**Safety Features:** *Patented Concealed Bearings,  
 Patented Concealed Drive & Tail Rolls,  
 Patented Boltless, Bearing Slide Mounts*