



POWER-PACK® Standard Conveyors - built the way you want them...

Field Info Required		Data	Field Info Required		Data
A.	Conveyor Length O.A.		Total Load On Conveyor		
B.	Belt Width		Belt Speed In Fpm		
C.	Height T.O.B. (Top of Belt)		Power: Volts, Phase, Hz		
M.	Top of Belt @ Bottom		S.	Conveyor Angle	

Product Being Carried:

Adverse Condition If Any:

Power-Pack will size for application

Dimensions		Belt Width +	Light	Medium	Heavy
Chain Size:			2.5"	4"	6"
D.	Body Height		10.25"	15.25"	22.25"
E.	Body Width O. A.	Belt +	4.75"	5.875"	6.875"
F.	Tail End Width O. A.	Belt +	10.25"	11.25"	13.5"
G.	Drive End Width O. A.	Belt +	19.5"	20.25"	22.5"
H.	Belt Tension Take Up Adjustment		5"	7.5"	11"
Q.	Load Height (Top of Flapper)	M. +	5"	5"	5"
Drive & Tail Sprocket:			5"	8"	12"
Cleats: Standard Height: Welded Top of Plate			1.5"	2.5"	4"
P.	Side Wings Height:		1.5"	2.5"	4"

Standard Features

Body Construction : Mild Steel	Belt Lacers: Pin
Belt Type : Plain Steel	Return Idlers: Greased Packed Bearings
Motor-Reducer Style : TEFC-Shaft Mounted	Leg Support: Tri-Lock H style
Motor Location : Left Side	Cleats: 3/16" Plate, welded
Bearings : Greased Sealed, Self Aligning	

See options section for additional features

Power-Pack® Conveyor Company
 38363 Airport Parkway • Willoughby, OH 44094
 Phone: (440) 975-9955 • Fax: (440) 975-0505
 Website: www.power-packconveyor.com
 Email: ppcc@power-packconveyor.com



Safety Features: Patented Concealed Bearings,
 Patented Concealed Drive & Tail Rolls,
 Patented Boltless, Bearing Slide Mounts