



POWER-PACK® Standard Conveyors - built the way you want them...

Field Info Required	Data	Field Info Required	Data
A. Conveyor Length O.A.		Total Load On Conveyor	
B. Belt Width		Belt Speed In Fpm	
C. Height T.O.B.(Top of Belt)		Power: Volts, Phase, Hz	
C-C. Length of Chute		O. Inlet Opening Length	
Product Being Carried:			
Adverse Condition If Any:			
Power-Pack will size for application			

Dimensions		Belt Width +	Light	Medium	Heavy
D.	Body Height		12.25"	14.25"	16.25"
E.	Body Width O. A.	Belt +	0.75"	0.75"	0.75"
F.	Tail End Width O. A.	Belt +	5"	7"	7.75"
G.	Drive End Width O. A.	Belt +	14"	16"	16.75"
H.	Belt Tension Take-Up Adjustment		2.5"	5"	11"
	Drive & Tail Pulley: Crowned		4.5"	6.625"	8.625"
I.	Belt Flat (Pocket)	Belt -	8"	8"	8"
J.	Flange Sides		4"	4"	4"
U.	Distance to Inlet Opening Min.:		20"	24"	36"

Standard Features			
Body Construction : Mild Steel		Bed Type : Slider	
Belt Type : PVC		Belt Lacers: Clipper Lacer	
Motor-Reducer Style : TEFC-Shaft Mounted		Return Idlers: Greased Packed Bearings	
Motor Location : Left Side		Leg Support: Tri-Lock H style	
Bearings : Greased Sealed, Self Aligning			
See options section for additional features			

Power-Pack® Conveyor Company
38363 Airport Parkway • Willoughby, OH 44094
Phone: (440) 975-9955 • Fax: (440) 975-0505
Website: www.power-packconveyor.com
Email: ppcc@power-packconveyor.com



Safety Features: Patented Concealed Bearings,
Patented Concealed Drive & Tail Rolls,
Patented Boltless, Bearing Slide Mounts